

	PCW5000
Series	Pro
Designed in	2003
Motor/Engine	POWERED by HONDA Honda GXH50 4-stroke air-cooled 1.6 kW - 2.1 HP @ 7,000 tr/min
Powered by	Gas
Drive/Clutch	Direct drive (no clutch)
Rope Retention System	No
Drum turns when motor/engine is idling	Yes
Pulling Capacity	
Standard drum (single line / double line)	Ø 2-1/4" (57 mm) : 2,200 lb / 4,400 lb
Optional drum (single line / double line)	Ø 3-3/8" (85 mm): 1,600 lb / 3,200 lb
Lifting Capacity	
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL SEALES winches
Optional drum (single line / double line)	
Speed	
Standard drum	Ø 2-1/4" (57 mm) : 40'/min
Optional drum	Ø 3-3/8" (85 mm) : 60'/min
Weight	35 lb
Dimensions (overall)	14-5/8" x 14-3/8" x 14-3/8"
Gearbox	Aluminium alloy. Heat treated 3-stage spur gears. Mounted on ball bearings. Oil bath lubrication.
Gear ratio	110:1
Brake	Anti-reversing roller clutch bearing
Rope (not included) Length	Low stretch double braided polyester Unlimited
Minimum diameter	Ø 3/8" (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 1/2" (12 mm)
Included	Round polyester sling - 8'
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use Motor/Engine	1 year Honda International Warranty
Certification	